



HORIZONTAL CLOSED END BALER



Versatile and Productive

Max-Pak Delivers

- Quality
- Performance
- Confidence



Year after year, you can count on Max-Pak Horizontal Closed End Balers to deliver the performance you need when baling a variety of materials, from high grade papers, to post-consumer plastics, OCC, textiles, and all non-ferrous materials.

Max-Pak HCE balers are available in 28 different models and configurations, so there is sure to be one that fits your operation. Of course, custom requirements are always welcome, because we realize that “standard” doesn’t always fit. With Max-Pak’s heavy duty construction and our better-than-it-has-to-be approach to electrical and hydraulic components, your Max-Pak baler will deliver years of trouble free service. Max-Pak delivers – literally, too. Our factory technicians will deliver and install your baler, and then train your operators before the installation is complete.

Let Max-Pak deliver YOUR next baler, and a new level of confidence.



Max-Pak’s “streamlined” hopper is flat in the back, allowing for a much smaller footprint and cleaner installations.

HCE Features

- Heavy Wall Tubular Steel Frame
- AR 400 Floor and Platen
- Hydraulic Regenerative Circuit and Air/Oil Cooler for High Performance at Lower Oil Temperatures
- Up to 181,310 psi packing force
- NEMA 12 Electrical Panel and Control System
- Conforms to OSHA and ANSI Z245.5 Standards
- Full Factory Delivery, Installation and Training
- One Year Warranty on Parts and Labor

Factory Installation and Training are Available with Every Max-Pak Baler

MAX-PAK HORIZONTAL CLOSED END BALER SPECIFICATIONS

BALER MODEL	BALE SIZE	BALE WEIGHT (OCC)	CYCLE TIME (No Load)	MOTOR (STD)	PUMP	CYLINDER	SYSTEM PRESSURE	RAM FORCE	PLATEN PRESSURE	OIL CAPACITY	SHIPPING WEIGHT (Approx)
HCE 3060x30-7	30 x 42 x 60	Up to 1,100	14.89 Seconds	20hp 208/230/460v 3 phase	46 GPM	7" Bore 5" Rod 46" Stroke	3000 PSI	109,681 lbs.	93.27 PSI	180 Gallons	13,800 lbs.
HCE 3060x30-8	30 x 42 x 60	Up to 1,200	10.01 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 46" Stroke	3000 PSI	143,257 lbs.	121.82 PSI	180 Gallons	14,300 lbs.
HCE 3060x48-7	30 x 42 x 60	Up to 1,100	10.66 Seconds	30hp 208/230/460v 3 phase	60 GPM	7" Bore 5" Rod 64" Stroke	3000 PSI	109,681 lbs.	93.27 PSI	180 Gallons	15,000 lbs.
HCE 3060x48-8	30 x 42 x 60	Up to 1,200	13.93 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 64" Stroke	3000 PSI	143,257 lbs.	121.82 PSI	180 Gallons	16,500 lbs.
HCE 3060x60-7	30 x 42 x 60	Up to 1,100	12.66 Seconds	30hp 208/230/460v 3 phase	60 GPM	7" Bore 5" Rod 76" Stroke	3000 PSI	109,681 lbs.	93.27 PSI	180 Gallons	18,200 lbs.
HCE 3060x60-8	30 x 42 x 60	Up to 1,200	16.54 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 76" Stroke	3000 PSI	143,257 lbs.	121.82 PSI	180 Gallons	18,500 lbs.
HCE 3072x30-7	30 x 42 x 72	Up to 1,300	14.89 Seconds	20hp 208/230/460v 3 phase	46 GPM	7" Bore 5" Rod 46" Stroke	3000 PSI	109,681 lbs.	93.27 PSI	180 Gallons	13,950 lbs.
HCE 3072x30-8	30 x 42 x 72	Up to 1,400	10.01 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 46" Stroke	3000 PSI	143,257 lbs.	121.82 PSI	180 Gallons	15,500 lbs.
HCE 3072x48-7	30 x 42 x 72	Up to 1,300	10.66 Seconds	30hp 208/230/460v 3 phase	60 GPM	7" Bore 5" Rod 64" Stroke	3000 PSI	109,681 lbs.	93.27 PSI	180 Gallons	15,700 lbs.
HCE 3072x48-8	30 x 42 x 72	Up to 1,400	13.93 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 64" Stroke	3000 PSI	143,257 lbs.	121.82 PSI	180 Gallons	15,900 lbs.
HCE 3072x60-7	30 x 42 x 72	Up to 1,300	12.66 Seconds	30hp 208/230/460v 3 phase	60 GPM	7" Bore 5" Rod 76" Stroke	3000 PSI	109,681 lbs.	93.27 PSI	180 Gallons	18,800 lbs.
HCE 3072x60-8	30 x 42 x 72	Up to 1,400	16.54 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 76" Stroke	3000 PSI	143,257 lbs.	121.82 PSI	180 Gallons	16,300 lbs.
HCE 4260x48-8	42 x 42 x 60	Up to 1,500	13.93 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 64" Stroke	3000 PSI	143,257 lbs.	85.27 PSI	180 Gallons	21,500 lbs.
HCE 4260x60-8	42 x 42 x 60	Up to 1,500	16.54 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 76" Stroke	3000 PSI	143,257 lbs.	85.27 PSI	180 Gallons	23,000 lbs.
HCE 4260x72-8	42 x 42 x 60	Up to 1,500	19.15 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 88" Stroke	3000 PSI	143,257 lbs.	85.27 PSI	180 Gallons	25,000 lbs.
HCE 4260x72-9	42 x 42 x 60	Up to 1,600	15.47 Seconds	50hp 208/230/460v 3 phase	95 GPM	9" Bore 6" Rod 88" Stroke	3000 PSI	181,310 lbs.	107.92 PSI	350 Gallons	26,400 lbs.
HCE 4272x48-8	42 x 42 x 72	Up to 1,750	13.93 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 64" Stroke	3000 PSI	143,257 lbs.	85.27 PSI	180 Gallons	23,500 lbs.
HCE 4272x60-8	42 x 42 x 72	Up to 1,750	16.54 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 76" Stroke	3000 PSI	143,257 lbs.	85.27 PSI	180 Gallons	24,500 lbs.
HCE 4272x72-8	42 x 42 x 72	Up to 1,750	19.15 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 88" Stroke	3000 PSI	143,257 lbs.	85.27 PSI	180 Gallons	26,000 lbs.
HCE 4272x72-9	42 x 42 x 72	Up to 1,850	15.47 Seconds	50hp 208/230/460v 3 phase	95 GPM	9" Bore 6" Rod 88" Stroke	3000 PSI	181,310 lbs.	107.92 PSI	350 Gallons	27,200 lbs.
HCE 4860x48-8	48 x 42 x 60	Up to 1,700	13.93 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 64" Stroke	3000 PSI	143,257 lbs.	74.15 PSI	180 Gallons	23,500 lbs.
HCE 4860x60-8	48 x 42 x 60	Up to 1,750	16.54 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 76" Stroke	3000 PSI	143,257 lbs.	74.15 PSI	180 Gallons	24,300 lbs.
HCE 4860x72-8	48 x 42 x 60	Up to 1,750	19.15 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 88" Stroke	3000 PSI	143,257 lbs.	74.15 PSI	180 Gallons	25,100 lbs.
HCE 4860x72-9	48 x 42 x 60	Up to 1,800	15.47 Seconds	50hp 208/230/460v 3 phase	95 GPM	9" Bore 6" Rod 88" Stroke	3000 PSI	181,310 lbs.	93.85 PSI	350 Gallons	26,000 lbs.
HCE 4872x48-8	48 x 42 x 72	Up to 2,000	13.93 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 64" Stroke	3000 PSI	143,257 lbs.	74.15 PSI	180 Gallons	24,200 lbs.
HCE 4872x60-8	48 x 42 x 72	Up to 2,000	16.54 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 76" Stroke	3000 PSI	143,257 lbs.	74.15 PSI	180 Gallons	24,950 lbs.
HCE 4872x72-8	48 x 42 x 72	Up to 2,000	19.15 Seconds	30hp 208/230/460v 3 phase	60 GPM	8" Bore 5.5" Rod 88" Stroke	3000 PSI	143,257 lbs.	74.15 PSI	180 Gallons	25,800 lbs.
HCE 4872x72-9	48 x 42 x 72	Up to 2,150	15.47 Seconds	50hp 208/230/460v 3 phase	95 GPM	9" Bore 6" Rod 88" Stroke	3000 PSI	181,310 lbs.	93.85 PSI	350 Gallons	27,200 lbs.

The Max-Pak Difference

Since 1976, Max-Pak has been making quality balers and compactors for the waste industry. It was something we had to do. You see, we're also in the waste paper recycling business, and 30 years ago we couldn't find a baler that performed the way we needed. So we built our own.

Being in the waste business has its advantages when you're designing a baler. Not only do we understand the challenges and demands expected from a baler, we get to test and fine tune our ideas in a real working environment – our own.

For our other baler customers, it means they get the benefit of our front-line experience and our determination to only build the best. A Max-Pak baler is not good enough for our customers unless it's good enough for us.

At Max-Pak we take a personal interest in every machine we sell, and every customer we serve. It comes from our small town heritage. It's who we are. So it also makes sense that we deliver and install every baler ourselves, and then train your operators before we leave. We want you to be a friend and a Max-Pak customer for a long time. That's part of our small town, small company mentality.

But make no mistake. Max-Pak is no lightweight when it comes to balers. You'll find our equipment in some of the most demanding industries, with some of the most particular companies.

Our customers have come to know and trust Max-Pak for productivity, reliability, and integrity. So it's no surprise that over 90% of all Max-Pak balers ever built are still on the job. And we plan to keep it that way.

Max-Pak Offers A Full Line of Baling and Recycling Equipment

Call Us For More Information, or to Locate Your Nearest Dealer.



Auto-Tie Balers



Stamper Full Eject Balers



Full Eject Balers



Vertical Balers



Compactors



Two-Ram Balers



Answer Two-Ram Baler



Foam Balers



Waste Processing Equipment, Inc.

260 Dilbeck Road / P.O. Box 1047 • Rainsville, AL 35986

Toll Free: 800-225-6458

Fax: 256-638-8979 • Web Site: www.maxpakbalers.com • Email Sales: sales@maxpakbalers.com • Email Service: service@maxpakbalers.com